

App. Serial No. 09/519,727
New Docket No. STFD.057PA
Office Action Response and Amendment

In the Claims

Please amend the claims as indicated below in their complete listing.

1. (original) A method of canceling cross talk interference in a received data signal, the method comprising:
- receiving an input signal that includes a primary data signal and a superimposed cross-talk signal;
 - iteratively computing a probable cross talk signal and, therefrom, producing a plurality of iteratively computed probable cross talk signals; and
 - calculating the data signal based at least in part upon the iteratively computed probable cross talk signals converging toward the superimposed cross-talk signal.
2. (original) The method as recited in claim 1 further comprising iteratively computing a probable desired signal estimate, wherein the probable desired signal estimate are used in iteratively computing the probable cross talk estimate and in calculating the data signal.
- X 3. (original) The method as recited in claim 1 wherein the data signal is a multi-carrier signal.
- X 4. (original) The method as recited in claim 3 wherein the data signal is a discrete multi-tone signal.
- X 5. (currently amended) ~~The~~ A method as recited in claim 1 of canceling cross talk interference in a received data signal, the method comprising:
- receiving an input signal that includes a primary data signal and a superimposed cross-talk signal wherein the cross-talk signal is from an HPNA signal;
 - iteratively computing a probable cross talk signal; and
 - calculating the data signal based at least in part upon the iteratively computed probable cross talk signal.

REST AVAILABLE COPY

App. Serial No. 09/519,727
New Docket No. STFD.057PA
Office Action Response and Amendment

- + 6. (original) The method as recited in claim 1 wherein the data signal is a VDSL signal.
7. (original) A method of canceling cross talk interference in a received data signal, the method comprising:
- receiving a symbol block;
 - obtaining an estimate of symbols in the symbol block;
 - iteratively calculating an expected value for each symbol in the symbol block and therefrom, producing a plurality of iteratively calculated expected values; and
 - selecting symbol values based on the iteratively calculated expected values converging toward final expected values for each symbol.
8. (original) The method as recited in claim 7 wherein the calculating includes executing soft cancellation of the estimate or the expected value from a preceding calculation.
9. (original) The method as recited in claim 8 wherein soft cancellation includes subtracting the effect of the estimate from the symbol block to produce an estimate of an interference free value of the input symbol in the symbol block.
10. (currently amended) The A method as recited in claim 8 of canceling cross talk interference in a received data signal, the method comprising:
- receiving a symbol block;
 - obtaining an estimate of symbols in the symbol block;
 - iteratively calculating an expected value for each symbol in the symbol block including executing soft cancellation of the estimate or the expected value from a preceding calculation wherein soft cancellation includes subtracting the expected values from the symbol block to produce an estimate of an interference free value of the input symbol in the symbol block; and
 - selecting symbol values based on final expected values for each symbol.

BEST AVAILABLE COPY

App. Serial No. 09/519,727
New Docket No. STFD.057PA
Office Action Response and Amendment

11. (currently amended) ~~The A method as recited in claim 8 of canceling cross talk interference in a received data signal wherein the calculating includes the method comprising:~~

receiving a symbol block;

obtaining an estimate of symbols in the symbol block;

iteratively calculating an expected value for each symbol in the symbol block, and including

executing soft cancellation of the estimate or the expected value from a preceding calculation, and

calculating interference power to account for the uncertainty of the estimate; and

selecting symbol values based on final expected values for each symbol.

12. (original) The method as recited in claim 11 wherein the calculating includes computing a plurality of probable values, the probable values being based at least in part on the calculated interference power and the soft cancellation.

13. (original) The method as recited in claim 12 wherein the calculating includes determining the expected value from the plurality of probable values.

14. (original) The method as recited in claim 13 wherein the symbol block includes primary data signal symbols and superimposed cross talk signal symbols.

15. (original) The method as recited in claim 14 wherein the primary data signal is a discrete multitone signal.

16. (original) The method as recited in claim 15 wherein at least one tone of the multi-tone signal is zeroed to produce better performance of soft cancellation.

App. Serial No. 09/519,727
New Docket No. STFD.057PA
Office Action Response and Amendment

17. (currently amended) ~~The A method as recited in claim 16~~ of canceling cross talk interference in a received data signal, the method comprising:

receiving a symbol block including primary data signal symbols and superimposed cross talk signal symbols wherein the primary data signal is a discrete multitone signal and wherein at least one tone of the multi-tone signal is zeroed to produce better performance of soft cancellation and wherein the tones that are zeroed are the ones with the largest interference from the superimposed cross talk signal;

obtaining an estimate of symbols in the symbol block;

iteratively calculating an expected value for each symbol in the symbol block including

executing soft cancellation of the estimate or the expected value from a preceding calculation,

calculating interference power to account for the uncertainty of the estimate,

computing a plurality of probable values, the probable values being based at least in part on the calculated interference power and the soft cancellation,

determining the expected value from the plurality of probable values; and selecting symbol values based on final expected values for each symbol.

18. (original) The method as recited in claim 14 wherein the primary data signal is a VDSL signal.

BEST AVAILABLE COPY

App. Serial No. 09/519,727
New Docket No. STFD.057PA
Office Action Response and Amendment

19. (currently amended) ~~The A method as recited in claim 14 of canceling cross talk interference in a received data signal, the method comprising:~~

receiving a symbol block including primary data signal symbols and superimposed cross talk signal symbols wherein the superimposed cross talk signal is an HPNA signal;

obtaining an estimate of symbols in the symbol block;

iteratively calculating an expected value for each symbol in the symbol block including

executing soft cancellation of the estimate or the expected value from a preceding calculation,

calculating interference power to account for the uncertainty of the estimate,

computing a plurality of probable values, the probable values being based at least in part on the calculated interference power and the soft cancellation,

determining the expected value from the plurality of probable values; and selecting symbol values based on final expected values for each symbol.

20. (original) The method as recited in claim 8 wherein a group of at least two symbols are used when performing soft cancellation.

21
Cont.
BEST AVAILABLE COPY

App. Serial No. 09/519,727
New Docket No. STFD.057PA
Office Action Response and Amendment

21. (original) A method for removing cross talk interference due to a cross talk source that undesirably interferes with the reception of data being transmitted over a transmission medium by coupling to the transmission medium, the method comprising:

receiving an input signal including a first signal that is superimposed on a second signal, the received signal having a symbol block with input symbols that include a first set of symbols associated with the first signal a second set of symbols associated with the second signal;

producing an estimate for the input symbols;

subtracting the effects of the input symbols from the received symbol block;

computing a probability distribution for each of the input symbols, the computing being based at least in part on the estimate;

calculating a weighted average from the probability distribution, the weighted average indicating a more likely value for the input symbols.

22. (currently amended) The method as recited in claim 2021 wherein the computing is based at least in part on a calculated interference power.

23. (currently amended) The method as recited in claim 2021 further including outputting the expected values for each of the symbols of the second signal.

24. (currently amended) The method as recited in claim 2021 wherein the weighted average is the estimate.